

2
0
2
2

CAL FIRE WUI CERTIFIED PRODUCTS BROCHURE



WHAT IS WUI?

DIGI DOCS SHEET

DIGITAL BROCHURE ACCESS

WUI CERTIFICATION DOCUMENTS



TABLE OF CONTENTS

03	8140-2084:0001 EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)
06	RESOURCES: DIGITAL DOCS
07	8110-2084:0002 DECKING FOR WILDLAND URBAN INTERFACE (WUI)
09	8140-2084:0003 EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)
12	RESOURCES: YOUR SAFETY
13	8140-2084:0004 EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)
15	8140-2084:0005 EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)
18	RESOURCES: MORE WESTERN WOODS PUBLICATIONS
19	8140-2084:0006 EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)
22	WESTERN WOODS WUI-CERTIFIED PRODUCTS

CONNECT WITH US

MAIL US

275 Sikorsky Ave. | Chico, CA 95973 || P.O. Box 4402 | Chico, CA 95927

CALL US OR VISIT US ONLINE

Tel (800) 824-4100

(800) 822-8157

Fax (800) 894-8601

www.westernwoodsinc.com

info@westernwoodsinc.com



PRODUCT

EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

AVAILABLE PROFILES

- > V SHIPLAP
- > CHANNEL SHIPLAP
- > SHIPLAP
- > TONGUE + GROOVE
- > LOG CABIN



◀ Scan the QR code to the left to get a digital copy of this document.
Access the QR codes for all of our products on **PAGE 06** or by visiting our website at westernwoodsinc.com.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 8140-2084:0001 Page 1 of 2

CATEGORY: 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

LISTEE: WESTERN WOODS INC.P.O. Box 4402, Chico, CA 95973-4402
Contact: Kevin Richter (530) 343-5821 Fax (530) 343-3851
Email: kevinr@westernwoodsinc.com

DESIGN: Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertical orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022**

Listing Expires

2023

Authorized By: **VICTOR WONG, Program Coordinator**

Fire Engineering Division

and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name. Model number, rating and SFM label.

APPROVAL: Listed as solid wood sidings for use in the Wildland Urban Interface areas.

XLF: 8140-2041:0001

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022**

Listing Expires

2023

Authorized By: **VICTOR WONG**, Program Coordinator


Fire Engineering Division

DIGITAL CERTIFICATE ACCESS

To get a digital copy of our WUI Certification documentation for easy print or distribution, simply scan the QR Codes below. If you have any additional questions about these products, please call a member of our sales team at (800) 824-4100 or visit westernwoodsinc.com.


8140-2084:0001

WALL SHEATING | PG 03




8140-2084:0004

WALL SHEATING | PG 13




8140-2084:0002

DECKING | PG 07



8140-2084:0005

WALL SHEATING | PG 15




8140-2084:0003

WALL SHEATING | PG 09



8140-2084:0006

WALL SHEATING | PG 19



HOW TO USE THE QR CODE 1. Unlock your device 2. Open your camera app. 3. Hold your camera over the QR Code. 4. Click on the pop-up



PRODUCT

DECKING FOR WILDLAND URBAN INTERFACE (WUI)

8140-2084:0002



◀ Scan the QR code to the left to get a digital copy of this document.
Access the QR codes for all of our products on **PAGE 06** or by visiting our website at westernwoodsinc.com.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 8110-2084:0002 Page 1 of 1

CATEGORY: 8110 -- DECKING FOR WILDLAND URBAN INTERFACE (W.U.I.)

LISTEE: WESTERN WOODS INC.P.O. Box 4402, Chico, CA 95973-4402
Contact: Kevin Richter (530) 343-5821 Fax (530) 343-3851
Email: kevinr@westernwoodsinc.com

DESIGN: Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:

Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.

Refer to the manufacturer's installation instructions and product data sheets.

RATING: Class B Flame Spread

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name. Model number, rating and SFM label.

APPROVAL: Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

XLF: 8110-2041:0002

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022** Listing Expires **2023**

Authorized By: **VICTOR WONG, Program Coordinator**
Fire Engineering Division



PRODUCT

EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

AVAILABLE PROFILES

- > V SHIPLAP (EDGE VEE)
- > CHANNEL SHIPLAP
- > SHIPLAP
- > TONGUE + GROOVE



◀ Scan the QR code to the left to get a digital copy of this document.
Access the QR codes for all of our products on **PAGE 06** or by visiting our website at westernwoodsinc.com.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 8140-2084:0003 Page 1 of 2

CATEGORY: 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

LISTEE: WESTERN WOODS INC.P.O. Box 4402, Chico, CA 95973-4402
Contact: Kevin Richter (530) 343-5821 Fax (530) 343-3851
Email: kevinr@westernwoodsinc.com

DESIGN: Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.

b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Groove or overlapping edge for shiplap designs.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance with Chapter 7A of the California Building Code.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022** Listing Expires **2023**

Authorized By: **VICTOR WONG**, Program Coordinator
Fire Engineering Division

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name. Model number, rating and SFM label.

APPROVAL: Listed as solid wood sidings for use in the Wildland Urban Interface areas.

XLF: 8140-2041:0003

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022**

Listing Expires

2023


Authorized By: **VICTOR WONG**, Program Coordinator
Fire Engineering Division

YOUR SAFETY MATTERS TO US.

Minimizing our environmental impact is not our only sustainability goal here at Western Woods. Keenly aware that more and more people are moving and building into the **Wildland-Urban Interface (WUI)**, our team has proactively sought out methods to produce lumber products that increase survivability in environmental events such as wildfires. Whether it is a home, a commercial structure, or a simple outbuilding, every moment of structural survivability in the face of disaster matters.

With that goal in mind, we are proud to announce that all of our Premium Designs products* have been produced to comply with the rigorous standards outlined in the **WUI Products Handbook**. Published by the California State Fire Marshal (SFM) as a supplemental part of the California Building Code (CBC), the WUI Products Handbook outlines all of the products that have been reviewed by the SFM Staff and had their compliance verified based upon thorough analysis of product performance test results and product reliability features. Every WUI verified product is listed and a listing number is then attached to the product.

To learn more about the Wildland-Urban Interface, check out their website at www.fire.ca.gov or by scanning the QR code to the right. To get a listing of our WUI compliant products, please visit our website at westernwoodsinc.com.



*This includes, ENDURAWOOD™ and PROFORMAWOOD™ lumber products. Additional, non Premium Designs products listed as well. See our website for details.

HOW TO USE THE QR CODE



1. Unlock your device



2. Open the camera app on your device.



3. Hold your camera over the QR Code.



4. Click on the pop-up window.



PRODUCT

EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

AVAILABLE PROFILES

> RABBETED BEVEL



◀ Scan the QR code to the left to get a digital copy of this document.
Access the QR codes for all of our products on **PAGE 06** or by visiting our website at westernwoodsinc.com.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 8140-2084:0004 Page 1 of 1

CATEGORY: 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

LISTEE: WESTERN WOODS INC.P.O. Box 4402, Chico, CA 95973-4402
Contact: Kevin Richter (530) 343-5821 Fax (530) 343-3851
Email: kevinr@westernwoodsinc.com

DESIGN: Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name. Model number, rating and SFM label.

APPROVAL: Listed as solid wood sidings for use in the Wildland Urban Interface areas.

XLF: 8140-2041:0004

11-23-11bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022**

Listing Expires

2023

Authorized By: **VICTOR WONG, Program Coordinator**

Fire Engineering Division



PRODUCT

EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

AVAILABLE PROFILES

> BOARD + BATTEN



◀ Scan the QR code to the left to get a digital copy of this document.
Access the QR codes for all of our products on **PAGE 06** or by visiting our website at westernwoodsinc.com.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 8140-2084:0005 Page 1 of 2

CATEGORY: 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

LISTEE: WESTERN WOODS INC.P.O. Box 4402, Chico, CA 95973-4402
Contact: Kevin Richter (530) 343-5821 Fax (530) 343-3851
Email: kevinr@westernwoodsinc.com

DESIGN: Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than 1/2", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name. Model number, rating and SFM label.

APPROVAL: Listed as solid wood sidings for use in the Wildland Urban Interface areas.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022**

Listing Expires

2023

Authorized By: **VICTOR WONG, Program Coordinator**

Fire Engineering Division

XLF: 8140-2041:0005

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022***Listing Expires***2023**Authorized By: **VICTOR WONG**, Program Coordinator*Fire Engineering Division*


WE HAVE WHAT YOU NEED FOR SUCCESS.



*PRODUCT &
SERVICES BROCHURE*



*LUMBER
PATTERN
BOOK*



*WOOD
PRODUCT
MINI BROCHURES*

*PRODUCT
LINE CARD*



GET YOUR DIGITAL COPIES AT WESTERNWOODSINC.COM.



PRODUCT

EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

AVAILABLE PROFILES

> BOARD ON BOARD



◀ Scan the QR code to the left to get a digital copy of this document.
Access the QR codes for all of our products on **PAGE 06** or by visiting our website at westernwoodsinc.com.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 8140-2084:0006 Page 1 of 2

CATEGORY: 8140 -- EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I.)

LISTEE: WESTERN WOODS INC.P.O. Box 4402, Chico, CA 95973-4402
Contact: Kevin Richter (530) 343-5821 Fax (530) 343-3851
Email: kevinr@westernwoodsinc.com

DESIGN: Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.

Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and 3/4" thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.

All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

RATING: Compliance with Chapter 7A of the California Building Code.

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee name. Model number, rating and SFM label.

APPROVAL: Listed as solid wood sidings for use in the Wildland Urban Interface areas.

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022**

Listing Expires

2023

Authorized By: **VICTOR WONG, Program Coordinator**

Fire Engineering Division

XLF: 8140-2041:0008

11-23-11 bh



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2022***Listing Expires***2023**Authorized By: **VICTOR WONG**, Program Coordinator*Fire Engineering Division*

DON'T JUST MAKE A HOME. MAKE A STATEMENT.

Great Looks That Last

ENDURAWOODs™ ability to firmly grip paint and stains gives you great looking siding, trim, and fascia that lasts and is easy to maintain.

ENDURAWOOD™

WESTERN WOODS PREMIUM FIR AND PINE PATTERNS + TRIM

At Western Woods we do not believe affordable building material should translate into sub-standard quality or performance. With **Western Woods ENDURAWOOD™ Premium Patterns + Trim** you will find a great wood product that strikes the right balance of strength, value, and quality appearance without breaking your budget.

PRODUCT HIGHLIGHTS

- ▶ Easily works with both hand and with power tools.
- ▶ Great for both indoor and outdoor projects.
- ▶ Available with primed, stained, or a natural finish.
- ▶ Available in both White Fir and Pine.
- ▶ Numerous pattern and finish options.

RECOMMENDED APPLICATIONS



Cornerboard



Trim



Fascia




Band



Fencing



Rake



Siding



Framing



Decking



ENDURAWOOD™ PROFORMAWOOD™

LUMBER WORTHY OF TURNING YOUR PROJECT INTO A MASTERPIECE.

Truly Awe-Inspiring

PROFORMAWOOD™ is made of top quality Western Red Cedar, delivering unparalleled versatility, performance, and beauty to any build project.

AVAILABLE OPTIONS



Natural

Will lose its color and silver over time.



Stained

You choose your color & finish.



Primed

StainBlock is applied for the top coat application.



Interior/Exterior

Both exterior & interior options available.



WWPA Patterns

WWPA Standard Patterns available upon request.



Custom Patterns

Custom patterns available upon request.

PROFORMAWOOD™

WESTERN WOODS PREMIUM WESTERN RED CEDAR PATTERNS + TRIM

Boasting a core of Western Red Cedar that produces nearly twice the stability of many other softwoods, our **PROFORMAWOOD™ Premium Western Red Cedar Patterns + Trim** delivers the professional grade longevity, performance, and aesthetics you need to make your next building project a success.

PRODUCT HIGHLIGHTS

- ▶ Boasts a strong natural resistance to moisture, decay, & insect damage.
- ▶ Easy to cut, saw, & nail thanks to a smooth, straight grain.
- ▶ Firmly grips onto paint and stains.
- ▶ Provides great style & performance.
- ▶ Great for a variety of both indoor and outdoor projects.

**WE ARE
WESTERN
WOODS™**



Tel (800) 824-4100

(800) 822-8157

Fax (800) 894-8601

MAIL US

275 SIKORSKY AVE.

CHICO, CA 95973

FIND US ONLINE:

www.westernwoodsinc.com

info@westernwoodsinc.com

LETS GET SOCIAL

Scan the QR Code with your phone or tablet
and join us on **LinkedIn** and **Facebook**.

LINKEDIN



FACEBOOK



GET A DIGITAL COPY

Did you know you can get a
digital copy of our brochure?
Get it now on our website.

SIGN UP FOR OUR NEWSLETTER

Scan this QR code with your phone or mobile
device and stay up to date with the news,
events, and product announcements happening
here at Western Woods.

MAILCHIMP

