

# 20<br/>20<br/>20WUI CERTIFIED<br/>PRODUCTS<br/>BROCHURE

FEATURING

WHAT IS WUI?

DIGI DOCS SHEET

**DIGITAL BROCHURE ACCESS** 

WUI CERTIFICATION DOCUMENTS

## 



#### Cal Fire

The California Office of the State Fire Marshal Fire Engineering team has reviewed the tecÛical documents for each of our products and deemed them acceptable to be included in the Cal Fire Building Materials Listing Program (BLM). Learn more at fire.ca.gov.



When the catastrophic Camp Fire wiped out the town of Paradise, the Butte County community - the community we call home was devastated. The disaster was a severe reminder of the sheer destructive power of wildfires. All of us came together to pick up the pieces, to help those that lost in the fire, and make strides toward a safer future. For us, wildfires are personal.

### **INTRODUCTION**

At Western Woods, we strive to deliver lumber products that offer industry-leading durability, safety, and performance. We're keenly aware that more and more people are building into the **Wildland-Urban Interface** (WUI) and the consequences that come with it. We take wildfires seriously, and for us, it's personal. Our team has experienced first-hand the effects of wildfires on our community. In response, our team has ambitiously pursued methods to produce lumber that offers increased survivability in environmental events such as wildfires. Whether your project is a home, a commercial structure, or a simple outbuilding, every moment your structure withstands a wildfire matters.

With that in mind, our team is proud to announce that our Premium Designs products\* have been produced to comply with the rigorous standards outlined in the **WUI Products Handbook**. Published by the **California State Fire Marshal** (SFM) as a supplemental part of the **California Building Code** (CBC)\*\*, the WUI Products Handbook outlines all of the products that have been reviewed by the SFM Staff and had their compliance verified based upon a thorough analysis of product performance test results and product reliability features. Every WUI-verified product is listed, and a listing number is then attached to the product.

To learn more about the visit the CalFire website at https://osfm.fire.ca.gov (or scan the QR code to the right). To complete get a listing of our WUI-compliant products, visit our website, www. westernwoodsinc.com, or turn to Page 027.



\* Including Western Woods ENDURAWOOD™ and PROFORMAWOOD™ lumber products. Additional, non Premium Designs products, have been listed as well. See our website for details.

\* WUI-Certified lumber products are now mandatory within the 2024 California Building Code (CBC).

## TABLE OFCONTENTS



### CONNECT WITH US

#### **VISIT OR MAIL US**

VISIT: 275 Sikorsky Ave. Chico, CA 95973 MAIL: P.O. Box 4402 Chico, CA 95927

#### CALL US OR VISIT US ONLINE

Tel (800) 824-4100 (800) 822-8157 Fax (800) 894-8601 www.westernwoodsinc.com info@westernwoodsinc.com

#### LET'S GET SOCIAL


- @westernwoodsinc
- f Western Woods, Inc.
- in Western Woods, Inc.



#### WUI-CERTIFIED PRODUCTS

001	<b>8140-2084:0001</b> EXTERIOR WALL SIDING AND SHEATHING
005	8110-2084:0002 Decking
009	<b>8140-2084:0003</b> EXTERIOR WALL SIDING AND SHEATHING
013	<b>8140-2084:0004</b> EXTERIOR WALL SIDING AND SHEATHING
017	<b>8140-2084:0005</b> EXTERIOR WALL SIDING AND SHEATHING
021	<b>8140-2084:0006</b> EXTERIOR WALL SIDING AND SHEATHING
024	WESTERN WOODS WUI-CERTIFIED PRODUCTS ENDURAWOOD™ AND PROFORMAWOOD™
RESO	OURCES
020	WUI // PRODUCTS Learn why wui products are better products.
026	WESTERN WOODS BROCHURES + GUIDES OUR LINEUP OF BROCHURES AND GUIDES TO TAKE YOU SUCCESS FURTHER.
027	<b>DIGITAL DOCS</b> CENTRALIZED QR CODE DIRECTORY FOR ALL PRODUCT

© 2021-2024 Western Woods, inc. All rights reserved. DOC VERSION 24.1.10



## EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

#### **AVAILABLE PROFILES**

> V SHIPLAP
> CHANNEL SHIPLAP
> SHIPLAP
> TONGUE + GROOVE

> LOG CABIN



 $\rightarrow$ 

Scan the QR code to get a digital copy of the certification document for this product.
QR codes for all of our WUI-certified products may be found on PAGE 027 or at westernwoodsinc.com.

001





#### LISTING SERVICE

LISTING No.:	8140-2084:0001
PARENT LISTING No.:	8140-2041:0001
	8140 - EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)
	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com
	Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.
	a. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap, Log Cabin: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 150 (Class C) when tested in accordance with ASTM E84.
	b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap: When applied in a vertica orientation with minimum nominal 6" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", "Ponderosa Pine", "Douglas Fir", "White Fir", and "Western Spruce", or any other wood species having a Flame Spread Rating not greater than 100 (Class C) when tested in accordance with ASTM E84.
	All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.

Page 1 of 2



#### LISTING SERVICE

RATING:	Compliance with Chapter 7A of the California Building Code.
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee name. Model number, rating and SFM label.
APPROVAL:	Listed as solid wood sidings for use in the Wildland Urban Interface areas.
NOTES:	

11-23-11 bh



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test resultsand/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria.Refer to listee's data sheet, installation instructions and/or other suitable information sources.

#### Date Issued: 05/05/2023

Authorized By: Victor Wong , Program Coordinator Fire Engineering & Investigations Division Listing Expires: 06/30/2024

8140-2084:0001 | SIDING

Page 2 of 2

## BY THE NUMBERS: WUSTATISTICS



The WUI is the fastest growing land use type in the United States.



97% of new WUI land was due to new home construction



80 million properties are at 'significant wildfire risk' in the WUI.



1 in 3 homes in the U.S. are located in the WUI.



Wildfires are more frequent, more intense, & are burning 2x longer.\*

TO LEARN MORE ABOUT WUI, VISIT THE CALIFORNIA OFSM WEBSITE: https://osfm.fire.ca.gov

0 0 4

4 WESTERN WOODS CALL US (800) 824-41



 $\rightarrow$ 

PRODUCT // No. 8110-2084:0002

## DECKING FOR WILDLAND URBAN INTERFACE (WUI)



Scan the QR code to get a digital copy of the certification document for this product.
QR codes for all of our WUI-certified products may be found on PAGE 027 or at westernwoodsinc.com.

005



#### LISTING SERVICE

LISTING No.:	8110-2084:0002
PARENT LISTING No	. 8110-2041:0002
CATEGORY:	8110 - DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
LISTEE:	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com
DESIGN:	Solid "Wood" decking, when installed over minimum 2" x 6" solid "Douglas Fir" or better joists, spaced 24" or less on center, and decking and joists complying with American Softwood Lumber Standard PS 20 as follows:
	Minimum nominal 5/4" thick and nominal 6" wide decking boards with a maximum 3/8" radius edges made of solid wood species"Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", or "Alaska Yellow Cedar" having a Class B Flame Spread rating when tested in accordance with ASTM E84. Lumber grades: construction common, commercial or better grades for Redwood; 3 common, commercial or better grades for Cedars.
	Refer to the manufacturer's installation instructions and product data sheets.
RATING:	Class B Flame Spread
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee name. Model number, rating and SFM label.
APPROVAL:	Listed as solid wood decking materials for use in the Wildland Urban Interface areas.

Page 1 of 2

Unbranded copies of this document are available for download at WESTERNWOODSINC.COM. Get it on your device instantly by scanning the QR Code on PAGE 027.

0 0 6



#### LISTING SERVICE

11-23-11 bh



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test resultsand/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria.Refer to listee's data sheet, installation instructions and/or other suitable information sources.

#### Date Issued: 05/05/2023

Authorized By: Victor Wong , Program Coordinator Fire Engineering & Investigations Division Listing Expires: 06/30/2024

Page 2 of 2

## WESTERN WOODS. WE OFFER: SHEATHING DECKING SDNG ENDURAWOOD<sup>™</sup> PROFORMAWOOD ТМ

### Call us today to learn more.

TO LEARN MORE ABOUT WUI, VISIT THE CALIFORNIA OFSM WEBSITE: https://osfm.fire.ca.gov

**NUI // STATISTICS** 

WESTERN WOODS

009

### **EXTERIOR WALL SIDING AND**

PRODUCT // No. 8140-2084:0003

## SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

#### AVAILABLE PROFILES

- > V SHIPLAP (EDGE VEE) > CHANNEL SHIPLAP
  - > SHIPLAP >> TONGUE + GROOVE



 $\rightarrow$ 

CAN HERE

Scan the QR code to get a digital copy of the certification document for this product.
QR codes for all of our WUI-certified products may be found on PAGE 027 or at westernwoodsinc.com.



#### LISTING SERVICE

LISTING No.:	8140-2084:0003
PARENT LISTING No.:	8140-2041:0003
CATEGORY:	8140 - EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)
LISTEE:	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com
DESIGN:	Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.
	a. Tongued & Grooved, Shiplap, V Shiplap (Edge Vee One Side): When applied in a horizontal orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84. An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for T&G or overlapping edge for shiplap designs.
	b. Tongued & Grooved, Shiplap, Channel Shiplap, V Shiplap (Edge Vee One Side): When applied in a vertical orientation with minimum nominal 4" wide and nominal 1" thick boards made of wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84 An additional face nail is to be added and shall be placed on the face, approximately 1" from the groove edge for the Tongue & Grove or overlaping edge for shiplap designs.
	All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.
RATING:	Compliance with Chapter 7A of the California Building Code.

Page 1 of 2



#### LISTING SERVICE

INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee name. Model number, rating and SFM label.
APPROVAL:	Listed as solid wood sidings for use in the Wildland Urban Interface areas.
NOTES:	

11-23-11 bh



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test resultsand/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria.Refer to listee's data sheet, installation instructions and/or other suitable information sources.


#### Date Issued: 05/05/2023

Listing Expires: 06/30/2024

Authorized By: Victor Wong , Program Coordinator Fire Engineering & Investigations Division 8140-2084:0003 | SIDING

Page 2 of 2

## WUI TRENDS: IT IS RAPIDLY EXPANDING ACROSS THE UNITED STATES.



TO LEARN MORE ABOUT WUI, VISIT THE CALIFORNIA OFSM WEBSITE: https://osfm.fire.ca.gov

GROWTH RATE OF HOMES IN THE WUI FROM 1990 TO 2010 BY STATE FOOM 1990 TO 2010 BY STAT

**NUI // TRENDS** 

0 1 2

WESTERN WOODS CALLUS (800) 824-4100 // VISITUS ONLINE www.westernwoodsinc.com

PRODUCT // No. 8140-2084:0004

## EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

**AVAILABLE PROFILES** 

> RABBETED BEVEL



 $\rightarrow$ 

SCAN HERE

Scan the QR code to get a digital copy of the certification document for this product.
QR codes for all of our WUI-certified products may be found on PAGE 027 or at westernwoodsinc.com.



#### LISTING SERVICE

LISTING No.:	8140-2084:0004
PARENT LISTING No.:	8140-2041:0004
CATEGORY:	8140 - EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)
LISTEE:	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com
DESIGN:	Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.
	Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.
	All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.
RATING:	Compliance with Chapter 7A of the California Building Code.
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee name. Model number, rating and SFM label.
APPROVAL:	Listed as solid wood sidings for use in the Wildland Urban Interface areas.

Page 1 of 2

Unbranded copies of this document are available for download at WESTERNWOODSINC.COM. Get it on your device instantly by scanning the QR Code on PAGE 027.

0 1 4



#### LISTING SERVICE

NOTES:

11-23-11bh



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test resultsand/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria.Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: 05/05/2023

Listing Expires: 06/30/2024

Authorized By: Victor Wong , Program Coordinator Fire Engineering & Investigations Division

8740-2084:0004

Page 2 of 2

## BUILD SMARTER. BUILD BETTER. **IT'S NOW CODE.**\*

Starting in California. Refer to the 2022 California Building Code, Title 24, Section 7A.

\* SOURCE 1: California Building Code 2022. Section 7A.https://www.dgs.ca.gov/en/BSC/Resources/2022-Title-24-California-Code-Changes/Part-2-Chapter-7A-Materials-and-Construction-Methods

TO LEARN MORE ABOUT WUI, VISIT THE CALIFORNIA OFSM WEBSITE: https://osfm.fire.ca.gov

WESTERN WOODS CALL US (800) 824-4100 // VISIT US ONLINE www.westernwoodsinc.com

016

PRODUCT // No. 8140-2084:0005

## EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

**AVAILABLE PROFILES** 

> BOARD + BATTEN



Scan the QR code to get a digital copy of the certification document for this product.

QR codes for all of our WUI-certified products may be found on PAGE 027 or at westernwoodsinc.com.

017



#### LISTING SERVICE

LISTING No.:	8140-2084:0005
PARENT LISTING No.:	8140-2041:0005
CATEGORY:	8140 - EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)
LISTEE:	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com
DESIGN:	Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.
	Board and Batten: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and minimum nominal 4" wide and nominal 1-1/4" thick battens, with boards installed with a gap not more than ½", with battens fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards and battens made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.
	All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.
RATING:	Compliance with Chapter 7A of the California Building Code.
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee name. Model number, rating and SFM label.

Page 1 of 2

Unbranded copies of this document are available for download at WESTERNWOODSINC.COM. Get it on your device instantly by scanning the QR Code on PAGE 027.

0 1 8



#### LISTING SERVICE

APPROVAL:	Listed as solid wood sidings for use in the Wildland Urban Interface areas.
NOTES:	

11-23-11 bh



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test resultsand/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria.Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: 05/05/2023

Authorized By: Victor Wong , Program Coordinator Fire Engineering & Investigations Division Listing Expires: 06/30/2024

Page 2 of 2

## WUI-CERTIFIED PRODUCTS EQUAL BETTER PRODUCTS.

WUI-Certified lumber products burn more slowly in the event of a fire, giving occupants the additional time they need to get what matters most out and to safety.

SOURCE 1: "Fueling the Flames." First Street Foundation. May 16, 2022. www.firststreet.org | SOURCE 2: "The Wildland-Urban Interface: The Problem, Trends, & Solutions." Headwater Economics. August 31, 2018. www.headwatereconomics.

TO LEARN MORE ABOUT WUI, VISIT THE CALIFORNIA OFSM WEBSITE: https://osfm.fire.ca.gov

PRODUCT // No. 8140-2084:0006

## EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (WUI)

**AVAILABLE PROFILES** 

> BOARD ON BOARD



 $\rightarrow$ 

+

CAN HERE

Scan the QR code to get a digital copy of the certification document for this product.

QR codes for all of our WUI-certified products may be found on PAGE 027 or at westernwoodsinc.com.

021



#### LISTING SERVICE

LISTING No.:	8140-2084:0006
PARENT LISTING No.:	8140-2041:0008
CATEGORY:	8140 - EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)
LISTEE:	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com
DESIGN:	Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.
	Board on Board: When applied in a vertical orientation with minimum nominal 8" wide and nominal 1" thick boards, and <sup>3</sup> / <sub>4</sub> " thick x 3-1/2" wide plywood inserts between boards, with boards and plywood inserts installed with a gap not more than 1/8" between them and fastened to the wood frame with not less than 3" long fasteners at a schedule not more than 24" on center, and boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.
	All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.
RATING:	Compliance with Chapter 7A of the California Building Code.
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING:	Listee name. Model number, rating and SFM label.

Page 1 of 2



#### LISTING SERVICE

APPROVAL:	Listed as solid wood sidings for use in the Wildland Urban Interface areas.
NOTES:	

11-23-11 bh



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test resultsand/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria.Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: 05/05/2023

Authorized By: Victor Wong , Program Coordinator Fire Engineering & Investigations Division Listing Expires: 06/30/2024

Page 2 of 2

**CERTIFIED PRODUCTS** 

## DON'T JUST MAKE A HOME. MAKE A STATEMENT.





#### **Great Looks That Last**

ENDURAWOODs™ ability to firmly grip paint and stains gives you great looking siding, trim, and fascia that lasts and is easy to maintain.

#### ENDURAVOOD WESTERN WOODS PREMIUM FIR AND PINE PATTERNS + TRIM

At Western Woods we do not believe affordable building material should translate into sub-standard quality or performance. With **Western Woods ENDURAWOOD™ Premium Patterns + Trim** you will find a great wood product that strikes the right balance of strength, value, and quality appearance without breaking your budget.


#### **PRODUCT HIGHLIGHTS**

Easily works with both hand and with power tools.

FREERE CLEBER

- Available with primed, stained, or a natural finish.
- Great for both indoor and outdoor projects.
- ► Available in both White Fir and Pine.
- Numerous pattern and finish options.

#### **RECOMMENDED APPLICATIONS**



CERTIFIED

ENDURAWOOD™ PRO

**CERTIFIED PRODUCTS** 

## LUMBER WORTHY OF TURNING YOUR PROJECT INTO A MASTERPIECE.

#### Truly Awe-Inspiring PROFORMAWOOD™ is made of top quality W<mark>estern</mark>

Red Cedar, delivering unparalleled versatility, performance, and beauty to any build project.

#### **AVAILABLE OPTIONS**



Natural

Will lose its color and silver over time.



Interior/Exterior

Both exterior & interior options available.



You choose your StainBlock

Stained

color & finish.

is applied for the top coat application.



**Custom Patterns** 

**Custom patterns** WWPA Standard available upon request.

WESTERN WOODS PREMIUM WESTERN RED CEDAR PATTERNS + TRIM

Boasting a core of Western Red Cedar that produces nearly twice the stability of many other softwoods, our **PROFORMAWOOD™ Premium** Western Red Cedar Patterns + Trim delivers the professional grade longevity, performance, and aesthetics you need to make your next building project a success.

#### PRODUCT HIGHLIGHTS

- Boasts a strong natural resistance to moisture, decay, & insect damage.
- Easy to cut, saw, & nail thanks to a smooth, straight grain.
- Firmly grips onto paint and stains.
- Provides great style & performacne.
- Great for a variety of both indoor and outdoor projects.

available upon request.

WWPA Patterns

Patterns

## WE HAVE WHAT YOU NEED FOR SUCCESS.

#### **PRODUCT &** SERVICES BROCHURE

COMPANY PROFILE | PRODUCT DESCRIPTIONS | Service Intros | Sustainability Outline



FAMILY. QUALITY. PASSION

#### LUMBER PATTERN BOOK



THE LUMBER THE LUMBER PATTERN BOOK DIAGRAMS FOR 70+ PATTERNS | INSTALLATION

INSTRUCTIONS | LUMBER CARE GUIDE



#### LUMBER PATTERN DATA SHEETS

70+ PATTERN SUMMARIES | PRODUCT SIZING OPTIONS | INSTALLATION INSTRUCTIONS



#### PRODUCT LINE CARD

PRODUCT SIZING | FINISH + PATTERN OPTIONS | DIGITAL DOCUMENT ACCESS

#### GET THESE AND MORE AT WESTERNWOODSINC.COM.

## DIGITAL CERTIFICATE **ACCESS**

To get a digital copy of our WUI Certification documentation for easy print or distribution, simply scan the QR Codes below. If you have any questions about our WUI-certified products, please call a member of our knowledgeable sales team at (800) 824-4100 or visit westernwoodsinc.com.

#### 8140-2084:0001 WALL SHEATING | PG 001



8110-2084:0002 DECKING | PG 005



8140-2084:0003 WALL SHEATING | PG 009



#### 8140-2084:0004 WALL SHEATING | PG 013



#### 8140-2084:0005 WALL SHEATING | PG 017



8140-2084:0006 WALL SHEATING | PG 021



HOW TO USE THE QR CODE 1. Unlock your device

2. Open your camera app. 3. Hold your camera over the QR Code. 4. Click on the pop-up

RESOURCES

2024 WUI CERTIFIED PRODUCTS BROCHURE

WE ARE WESTERN WOODS™

### **WESTERN WOODS**

Tel (800) 824-4100 (800) 822-8157 Fax (800) 894-8601

MAIL US CHICO, CA 95973

#### **FIND US ONLINE:**

www.westernwoodsinc.com info@westernwoodsinc.com

#### **LETS GET SOCIAL**

Scan the QR Code with your phone or tablet and join us on LinkedIn and Facebook.





#### **GET A DIGITAL COPY**

#### SIGN UP FOR OUR NEWSLETTER

device and stay up to date with the news, events, and product announcements happening here at Western Woods.







© 2021- 2024 Western Woods, Inc. All rights reserved. PROFORMAWOOD™, ENDURAWOOD™, PREMIUM DESIGNS™, and the Western Woods logo, and all associated materials are all property of Western Woods, inc.